

GEAQUELLO® E 234

Retrofit Modules

Description

The retrofit modules GEAQUELLO® E 234 consist of a flame-resistant and expanding fire protecting material based on polyurethane, which is non-toxic as well as fibre and solvent free. These modules ensure a smooth retrofitting of cables and pipes of any type and serve as placeholders in penetrations protected with GEAQUELLO® E 950 or CPS sealing systems.

Areas of Application

- Ships & Offshore
- Indoor and outdoor application
- Cable and pipe penetrations
- On request



Delivery and Packaging

GEAQUELLO® E 234			
	S	M	L
Packaging	box		
Module size Ø	40 × 235 mm	66 × 235 mm	90 × 235 mm
Quantity	20 pcs. / box	6 pcs. / box	3 pcs. / box
Weight	0.3 kg	0.75 kg	1.5 kg
Article number			
	4145500	4145502	4145504

Please contact us for further information:

☎ +49 4105-40 90-14

✉ transportation@svt.de

GEAQUELLO® E 234

Technical Data

Colour	black
Shore hardness (DIN 53505)	88–92 Shore A
Expansion pressure (300 °C)	0.6–1.2 N/mm ²
Expansion (450 °C)	17 to 26 fold
Processing temperature	-50 to +100 °C
Processing	<p>GEAQUELLO® E 234 retrofit modules are available in 40, 66, 90 mm diameters. Tested services: cables up to 37 mm; combustible pipes up to Ø 63 mm; metal pipes up to Ø 22 mm. The distance to the other components should be two layers of R 312 / R 380: The annular gap should be at least 8 mm after the drilling. It is filled with cartridge material of GEAQUELLO® E 234 T.</p>
Storage	Store in a cool and dry place.
Supply options	0.3 kg, 0.75 kg, 1.5 kg box
Certificates	<p>Product has MED approval according to IMO Patent Number: 10 2018 114 683.3.</p>